



भारत का राजपत्र The Gazette of India

प्राधिकार से प्रकाशित
PUBLISHED BY AUTHORITY

सं० 45] नई दिल्ली, शनिवार, नवम्बर 5, 1983 (कार्तिक 14, 1905)
No. 45] NEW DELHI, SATURDAY, NOVEMBER 5, 1983 (KARTIKA 14, 1905)

इस भाग में निम्न पृष्ठ संख्या दी जाती है, जिससे कि यह अलग संकलन के रूप में रखा जा सके ।
(Separate paging is given to this Part in order that it may be filed as a separate compilation)

भाग III—खण्ड 2
[PART III—SECTION 2]

(Notifications and Notices issued by the Patent Office relating to Patents and Designs)

29th September, 1983

- 1193/Cal/83. Shri Rabindra Nath Das. Inserted Two-in-one.
 1194/Cal/83. Diversified products Corporation. Adjustable bench mounted leg lift exerciser.
 1195/Cal/83. Union Carbide Corporation. Improved process for the preparation of carbofuran.
 1196/Cal/83. David Weston. Production of a purified aluminium mono-chloride from alumina, bauxites and clays and the subsequent production of aluminum metal.
 1197/Cal/83. Schlumberger Limited. Surface acoustic wave sensors.
 1198/Cal/83. Devinder Raj Bhasin. An everlasting match.
 1199/Cal/83. Fonderies Montupet. Process for the production of composite alloys based on aluminium and boron and application thereof.
 1200/Cal/83. ICI Americas Inc. A method of preparing 2-substituted-5-methyl-pyridines.

30th September, 1983

- 1201/Cal/83. Societe Nationale Industrielle Aerospatiale S.A., Tail rotor arrangement with increased thrust for rotary wing aircraft and a device for increasing the thrust of such a rotor arrangement.
 1202/Cal/83. The Babcock & Wilcox Company. Panel indicator.
 1203/Cal/83. The Boots Company PLC. Therapeutic Agents. (13th September, 1983).
 1204/Cal/83. The Boots Company PLC. Therapeutic Agents. (13th September, 1983).
 1205/Cal/83. John F. Krumme, Darel E. Hodgson and Ronald E. McAdams. Method of contraception and apparatus for carrying out such method.
 1206/Cal/83. Cummins Engine Company, Inc. Electronically controlled fuel pump.
 1207/Cal/83. Massey-Ferguson services N.V. Differential mechanisms (14th October, 1982).
 1208/Cal/83. Kennecott Corporation. Edge trimming and scrap disposal system.
 1209/Cal/83. Kennecott Corporation. Camber-monitoring tensiometer.

1st October, 1983

- 1210/Cal/83. Maschinenfabrik Rieter AG. Cleaning machine for fiber material.
 1211/Cal/83. Ambac Industries, Inc. Method and apparatus for indicating an operating characteristic of an internal combustion engine.
 1212/Cal/83. Ambac Industries, Inc. Method and apparatus for controlling diesel engine exhaust gas recirculation partly as a function of exhaust particulate level.
 1213/Cal/83. Kraftwerk Union Aktiengesellschaft. Steam turbine condenser having at least one stream bypass inlet.

3rd October, 1983

- 1214/Cal/83. Hitachi Ltd. Control method for induction motors.
 1215/Cal/83. Kennecott Corporation. Electrohydraulic drive for process line winders, unwinders and other equipment.
 1216/Cal/83. Kennecott Corporation. Cold rolling mill for metal strip.

- 1217/Cal/83. Kennecott Corporation. Two high hot rolling mill process and narrow strip product.
 1218/Cal/83. Ethicon Inc. Hard tissue surgical needle.
 1219/Cal/83. Texaco Development Corporation. Process and apparatus for recovery of water from dispersions of soot and water.
 1220/Cal/83. M/s. Steelsworth Pvt. Ltd. Improvements in/or relating to CTC machines in the processing of tea leaves.
 1221/Cal/83. Henry C. Lasater. Liquid degasification device.
 1222/Cal/83. Vickers Australia Limited. Abrasion Wear resistant steel.

4th October, 1983

- 1223/Cal/83. Intech systems Corp. Differential stethoscope.
 1224/Cal/83. Fairchild Camera and Instrument Corporation. Floating point microprocessor.
 1225/Cal/83. Tokyu Musashi Manufacturing Co. Ltd. Algal culturing unit, artificial reef unit and artificial culturing and fishing field unit.
 1226/Cal/83. Societe Des Electrodes ET Refractaires "Savole" (SERS). Continuous method of graphitising long carbon-containing products and a furnace for carrying out the method.
 1227/Cal/83. Transformatoren Union Aktiengesellschaft. A three-phase current choke with a five-limb core.
 1228/Cal/83. SKW Trostberg Aktiengesellschaft. Nitrogen fertiliser with a content of nitrification inhibitor.

5th October, 1983

- 1229/Cal/83. Westinghouse Electric Corporation. Improved vacuum interrupter contact material.
 1230/Cal/83. Westinghouse Electric Corporation. A static var generator having a thyristor circuit arrangement providing reduced losses.
 1231/Cal/83. Kennecott Corporation. Hot mill hydraulic direct roll drive.
 1232/Cal/83. Kennecott Corporation. Hot mill roll brushing system.
 1233/Cal/83. Kennecott Corporation. Hot mill self-centering roll design.
 1234/Cal/83. Minsky Motorny Zavod. Internal combustion engine.
 1235/Cal/83. Bigelow-Sanford, Inc., Shipping pallet and container.
 1236/Cal/83. Leeson Corporation. Method of an apparatus for furnishing strand to user means. [Divisional date 21st July, 1980].
 1237/Cal/83. Pont A. Mousson S.A. Method and apparatus for cutting oval pipes.

APPLICATIONS FOR PATENTS FILED AT PATENT OFFICE BRANCH, MUNICIPAL MARKET BUILDING, III FLOOR, KAROL BAGH, NEW DELHI-5.

5th September, 1983

- 604/Del/83. Kennametal Inc., "Milling cutter and indexable cutting insert therefor".
 605/Del/83. Kennametal Inc., "Multi-insert cutter bit".
 606/Del/83. Exxon Research and Engineering Company, "A process for separating at least one selected organic liquid from a feed comprising a mixture thereof" [Divisional date December 5, 1979].

6th September, 1983

- 607/Del/83. New Zealand Steel Limited, "Recovery of vanadium oxide".

608/Del/83. Poclair Hydraulics, "Pressurized fluid mechanism, motor or pump".

6th September 1983

609/Del/83. Compagnie Francaise Des Petroles. "Improvements in and relating to ocean platforms".

271/Bom/83. Cames Engineers Pvt. Lt. A drier.

272/Bom/83. Thermax Pvt. Ltd. Husk Burner.

610/Del/83. Clark & Vicario Corporation, "Deaerated liquid stock supply".

273/Bom/83. Thermax Pvt. Ltd. Incineration Furnace.

274/Bom/83. Thermax Pvt. Ltd. Incineration Furnace.

Typed or photo copies of the specifications together with photo copies of the drawings, if any, can be supplied by the Patent Office, Calcutta on payment of the prescribed copying charges which may be ascertained on application to that office.

CLASS : 32 F₂₀. 152155.
Int. Cl. : C 07 c 63/26.
D 06 m 1/00.

PROCESS FOR PREPARING TEREPHTHALIC ACID.

Applicants : LABOFINA S.A., OF 100, B-1120, BRUXELLES, BELGIUM.

Inventors : MR. JACQUES DANIEL VICTOR HANOTIER.

Application No. 757/Cal/1979 filed July 23, 1979.

Appropriate Office for Opposition Proceedings (Rule 4, Patents Rules, 1972) Patent Office, Calcutta.

19 Claims.

A process for preparing terephthalic acid which comprises the steps of :

(a) oxidizing a substantially homogeneous liquid reaction mixture comprising

— at least one oxidizable terephthalic acid precursor selected from the group consisting of p-toluic acid, and mixtures of p-toluic acid and an oxidizable compound selected from the group of p-xylene, partially oxidized p-xylene derivatives, and mixtures thereof,

— an amount of at least 5% by weight of water which is sufficient to obtain a workable slurry,

— an amount of an oxidation catalyst comprising at least one catalytically — active metal compound selected from the group consisting of manganese compounds, cobalt compounds, and mixtures thereof, such as hereinbefore described, which is sufficient to provide at least a minimum amount of M millimoles of the catalytically-active metal compound per kg of the liquid reaction mixture, wherein M is defined by the following equation (1)

$$M = \frac{y(x+A) + Bx}{Cx + D} \quad (1)$$

wherein y represents the molar ratio of water/p-toluic acid in the reaction mixture,

x represents the molar ratio of manganese/total amount of manganese + cobalt in the catalyst composition,

i.e.

$$\frac{Mn}{Mn + Co}$$

A equals about 0.200,
B equals about 10.9,
C equals about 4.35, and
D equals about 0.0724,

With a molecular oxygen-containing gas at a reaction temperature of from about 140°C to about 220°C and at a pressure sufficient to maintain at least part of the water in the liquid phase at the reaction temperature;

(b) recovering an oxidized mixture containing the terephthalic acid; and

(c) recovering the terephthalic acid from the above mixture by a process such as hereinbefore described.

(Compl. specn. 52 pages. Drg. 1 sheet).

CLASS : 70 B. 152156.
Int. Cl. : B 01 k 1/00, 3/02.

AN IMPROVED ELECTROLYTIC CELL.

Applicants : APPLIED SCIENCE RESEARCH INSTITUTE OF NO. 49, TANAKA-OOI-MACHI, SAKYO-KU, KYOTO-SHI, KYOTO, JAPAN AND NOBUATSU WATANABE OF

NO. 136, UGUISU-DAI, NAGAKAKYO-SHI KYOTO, JAPAN.

Inventors : KENICHI MORIGAKI AND NOBUATSU WATANABE.

Application No. 865/Cal/79 filed August 21, 1979.

Appropriate Office for Opposition Proceedings (Rule 4, Patents Rules, 1972) Patent Office, Calcutta.

7 Claims.

An improved electrolytic cell comprising a negative electrode having as the active material a light metal, an electrolyte and a positive electrode of a polycarbon fluoride, characterized in that the positive electrode contains as the main active material a polydicarbon monofluoride represented by the formula $(C_2F)_n$ wherein n is an integer and having a crystalline structure in which a layer structure is stacked with an inter-layer spacing of about 9.0 Å to form a packing structure, said crystalline structure exhibiting a peak at about 10° in terms of an angle of 2θ in the X-ray diffraction power pattern, and wherein said active material may contain conventional additives, if desired.

(Compl. specn. 27 pages. Drgs. 6 sheets).

CLASS : 167 H, 198 A. 152157.
Int. Cl. : B 07 b 1/00, 3/00.

MACHINE FOR CLEANING AND OR SORTING LOOSE MATERIALS.

Applicants : UKRAINSKY NAUCHNO-ISSLEDOVATELSKY INSTITUT MEKHAANIZATSII ELEKTRIFIKATSII SELSKOGO KHOZYAISTVA OF KIEVSKAYA OBLAST, VASILKOVSKY RAION, P. GLEVAKHA, 1, U.S.S.R.

Inventors : 1. EVGENY SERGEEVICH GONCHAROV-KIEV, 2. ANATOLY NAZAROVICH PRILUTSKY-KIEV, 3. VIKTOR IVANOVICH SHEVCHUK-KIEVSKAYA OBLAST, 4. VLADIMIR KONSTANTINOVICH MOISEENKO-KIEVSKAYA OBLAST.

Application No. 1137/Cal/79 filed October 30, 1979.

Appropriate Office for Opposition Proceedings (Rule 4, Patents Rules, 1972) Patent Office, Calcutta.

9 Claims.

A machine for cleaning and/or sorting loose materials, comprising at least one cleaning and/or sorting unit, a hollow casing of said unit secured to a frame, said casing accommodating arranged in a sequence a pneumatic separating duct provided with a spreader for loose material mounted therein, a rotor comprising a screen drum secured thereto, a distributor being provided at the top portion of said drum, screen cleaners installed outside of said drum and directly engaging it, a drive secured to the frame and imparting to the drum simultaneously rotary and oscillatory motions, each of said units communicating with an aspiration chamber, said screen drum being of composite design and consisting of a plurality of series-arranged sections and each of said sections comprising a screen in the form of a body of revolution, said screen being secured to support rings, and all sections being interconnected by means of equally spaced tierods extending through said support rings, said screen cleaners being installed diametrically opposite to one another with respect to the axis of rotation of said drum.

(Compl. specn. 39 pages. Drgs. 4 sheets).

CLASS : 9 F. 152158.
Int. Cl. : C 22 c 1/06.

DIRECT METHOD FOR PRODUCTION OF HIGH-GRADE, HIGH PURITY FERROMANGANESE.

Applicants : PACIFIC METALS CO., LTD. OF No. 6-1, 1-CHOME, OTEMACHI, CHIYODAKU, TOKYO, JAPAN.

Inventors : 1. YOSHISHIGE NAGOYA, 2. KOSUKE MURAI, 3. HIROTA AMANO AND 4. YOSHISADA SOGA.

Application No. 1143/Cal/79 filed November 2, 1979.

Appropriate Office for Opposition Proceedings (Rule 4, Patents Rules, 1972) Patent Office, Calcutta.

4 Claims.

A direct method for production of high-grade high-purity ferromanganese comprising the steps of charging a molten Mn-containing material, a non-carbonaceous reducing agent and a slagging material in a reaction vessel and subjecting the reaction vessel to horizontal eccentric circular motion to mix and agitate the contents of the vessel, whereby the Mn-oxide contained in the molten Mn-containing material is reduced by the non-carbonaceous reducing agent.

(Compl. specn. 20 pages. Drg. Nil.

CLASS : 129 G. 152159.
Int. Cl. : B 23 d 47/00.

METAL DISC SAW.

Applicants : ROLF PEDDINGHAUS OF DETERBERGER STRASSE 25, 5828 ENNEPITAL, WEST GERMANY.

Inventors : 1. BERND STURSBURG AND 2. HUBERT BARYSCH.

Application No. 1188/Cal/79 filed November 15, 1979.

Appropriate Office for Opposition Proceedings (Rule 4, Patents Rules, 1972) Patent Office, Calcutta.

9 Claims.

A metal disc saw for selectively cutting wide workpieces obliquely and perpendicularly with respect to their length comprising a machine frame which is pivotable about, and securable relative to a workpiece stop provided with a slit for the saw to pass there through, and wherein a tool slide, complete with drive, gearing and sawblade, is movable from a starting position occupied prior to execution of a sawcut in order to execute said cut, wherein the starting position of the sawblade is on the opposite side of the work stop to that which abuts the workpiece and wherein the cutting direction is opposite to the direction of feed, the tool slide being guided in the horizontal direction with the sawblade axis above the workpiece.

(Compl. specn. 13 pages. Drgs. 3 sheets).

CLASS : 107 H. 152160.
Int. Cl. : F 02 m 47/00, 61/18.

FUEL INJECTION NOZZLES.

Applicants : LUCAS INDUSTRIES LIMITED OF GREAT KING STREET, BIRMINGHAM B19 2XF, ENGLAND.

Inventors : PETER HOWES.

Application No. 1192/Cal/79 filed November 17, 1979.

Convention date 17th November, 1978 (45088/78) U.K.

Appropriate Office for Opposition Proceedings (Rule 4, Patents Rules, 1972) Patent Office, Calcutta.

9 Claims.

A fuel injection nozzle for supply fuel to a compression ignition engine comprising a hollow body part, a valve assembly including a resiliently loaded valve member and a seating, the valve assembly being located within the body part with a valve head forming part of the assembly being exposed at or beyond one end of the body part, and a fuel inlet communicating with the interior of the body part, the arrangement being such that in use, when fuel under pressure is supplied to the inlet, the fuel pressure within the body part acting upon the components of the valve assembly will effect movement of the valve head away from the body and the seating to permit fuel to flow past the valve head and seating into in use, the respective combustion chamber of the associated engine, the nozzle being characterized by an annular elongated part located within the body part, said elongated part surround-

ing the portion of the valve assembly lying within the body part, said elongated part acting to define part of the wall of a chamber to which fuel under pressure is supplied from the inlet and from which fuel flows when the head is moved out of contact with the seating, the wall thickness of said elongated part being such that the wall deflects during the initial delivery of fuel to the nozzle thereby to store part of the initial flow of fuel whereby the initial rate of flow of fuel past the valve head and seating will be at a reduced rate.

(Compl. specn. 10 pages. Drgs. 2 sheets).

CLASS : 73. 152161.
Int. Cl. : D 06 45/08, 45/18.

SQUEEZE ROLL ADAPTED TO ADJUST WIDTHWISE DISTRIBUTION OF PRESSURE ON CLOTH BEING TREATED IN A SPREAD STATE.

Applicants : WAKAYAMA IRON WORKS, LIMITED OF NO. 4, 2-CHOME, MINAMI-KATAHARA, WAKAYAMA-SHI WAKAYAMA-KEN, JAPAN.

Inventors : HIROSHI AZUMA.

Application No. 1248/Cal/79 filed November 28, 1979.

Appropriate Office for Opposition Proceedings (Rule 4, Patents Rules, 1972) Patent Office, Calcutta.

7 Claims.

A squeeze roll adapted to adjust the widthwise distribution of pressure on cloth being treated in a spread state, comprising a support shaft journaled at its opposite ends having a shaft axis with ends, a cylindrical tube coaxially fixed to said support shaft at the central portion thereof having a tube axis with ends, conical pistons having conical heads and rotatably and slidably mounted on opposite ends of said shaft, interior conical guide members formed on the inner surface of said cylindrical tube at the opposite ends thereof & adapted to be contacted with the conical heads of said pistons, and thrust means mounted on the opposite ends of said support shaft for imparting an axially adjustable force to said pistons, the arrangement being such that said shaft axis ends are offset from said tube axis ends and the pressure of contact between said conical heads and said conical guide member is adjustable whereby said conical pistons eccentrically load said guide members, thereby bending said tube.

(Compl. specn. 13 pages. Drgs. 3 sheets).

CLASS : 62 C, 154 D. 152162.
Int. Cl. : C 09 b 67/00; D 06 p 1/02.

AQUEOUS AZO DIRECT DYESTUFF FORMULATION AND A PROCESS FOR ITS PREPARATION.

Applicants : CASSELLA AKTIENGESSELLSCHAFT OF 526, HANAUER LANDSTRASSE, 6000 FRANKFURT/MAIN-61, WEST GERMANY.

Inventors : 1. WOLFGANG BAUER, 2. HEINZ DICKMANN, 3. KONSTANTIN MORGENROTH, 4. KUNO REH AND 5. JOACHIM RIBKA.

Application No. 47/Cal/80 filed January 14, 1980.

Appropriate Office for Opposition Proceedings (Rule 4, Patents Rules, 1972) Patent Office, Calcutta.

11 Claims.

Aqueous azo direct dyestuff formulation containing at least one polyazo direct dyestuff of the group selected, such that it contains 3 azo bonds and 2 to 4 groups conferring solubility in water and such that it contains 4 azo bonds and at least two groups conferring solubility in water, which polyazo dyestuff is stable to alkali and contains within an aromatic ring at least one hydroxy group, a compound exhibiting an alkaline reaction, namely a tertiary alkali metal phosphate and/or an alkali metal metasilicate and/or alkali metal hydroxide and

optionally a hydrotropic compound characterised in that the said dyestuff formulation has a pH value equal to or greater than 12 and a dyestuff concentration of 5 to 50% by weight.

(Compl. specn. 19 pages. Drgs. 2 sheets).

CLASS : 172 F. 152163.
Int. Cl. : D 02 g 1/00 & 3/00.

APPARATUS FOR PRODUCING A BOUND YARN.

Applicants : SCHUBERT & SALZER MASCHINENFABRIK AKTIENGESellschaft OF FRIEDRICH-EBERT-STRASSE 84, 8070 INGOLSTADT, GERMANY.

Inventors : 1. ERICH BOCK, 2. EUGEN HINI, 3. BURKHARD WULFHORST AND 4. BERNHARD GRUPP.

Application 57/Cal/80 filed January 16, 1980.

Appropriate Office for Opposition Proceedings (Rule 4, Patents Rules, 1972) Patent Office, Calcutta.

10 Claims.

Apparatus for producing a bound yarn, which consists of a sliver round which a binding thread is wound, and having a hollow spindle mounted between a pair of delivery rollers and a pair of draw-off rollers, with a rotating binding thread bobbin arranged coaxially of the hollow spindle, and with a housing which surrounds the binding thread bobbin, characterized in that the housing is stationarily arranged and is closed off by a cover which comprises a bore lying centrally of the hollow spindle; and means for building up an air pressure in the housing, in the vicinity of the bore, by an air current which can be produced in the housing and/or can be introduced into the housing, the magnitude of this air pressure being at least equal to or greater than the external pressure surrounding the bore.

(Compl. specn. 19 pages. Drgs. 2 sheet).

CLASS : 27 E. 152164.
Int. Cl. : E 04 b 5/54,
E 04 c 2/14.

CONSTRUCTION ELEMENTS : PROCESS AND DEVICE FOR MANUFACTURING SAME.

Applicants : ISOVER SAINT-GOBAIN OF 63, RUE DE VILLIERS, F92209 NEUILLY SUR SEINE, FRANCE.

Inventors : 1. YVES BUCK AND 2. ADRIEN DELCOIGNE.

Application No. 168/Cal/80 filed 14 February, 1980.

Appropriate Office for Opposition Proceedings (Rule 4, Patents Rules, 1972) Patent Office, Calcutta.

25 Claims.

A construction element of plaster and like, in the form of a plate comprising reinforcements distributed in the greater part of its thickness, characterised in that along lines parallel to the upper and lower surfaces of the plate the reinforcements are concentrated in a predetermined zone of the thickness of the plate, such that the plaster may be removed plumb with these lines thus forming folding lines to produce a non-planner construction element.

(Compl. specn. 22 pages. Drgs. 5 sheets).

CLASS : 47 A. 152165.
Int. Cl. C 10 b 47/00.

PROCESS FOR THE PRODUCTION OF COKE.

Applicants : CHARBONNAGES DE FRANCE OF 9 AVENUE PERCIER, 75008 PARIS, FRANCE AND HOUILLERES DU BASSIN DU NORD ET DU PAS-DE-CALAIS OF 64 RUE DES MINIMES, 59500 DOUAL (NORD), FRANCE.

Inventors : GEORGES PRUDHON AND JACK VERLAINE.

Application No. 576/Cal/80 filed May 14, 1980.

Appropriate Office for Opposition Proceedings (Rule 4, Patents Rules, 1972) Patent Office, Calcutta.

14 Claims.

Process for production of coke comprising the preparation according to a known method of a mixture based on constituent coal fines with particle sizes such that 80% have dimensions of less than about 2 mm, containing non-coking or poorly coking coals having a swelling index of not more than 5, at least some of the constituent coal fines being agglomerated in a press after addition of a tar pitch or bitumen having a KS point of about 70 to 85°C, said mixture being intended to be charged into a coke oven chamber, wherein at least some of the obtained agglomerates are recrushed to a particle size such that 50% have dimensions less than 5 mm, before said charging into the coke oven chamber.

(Compl. specn. 21 pages. Drgs. Nil).

CLASS : 172 C1. 152166.
Int. Cl. : D 01 g 15/84.

A CARD CLOTHING FOR CARDING MACHINES.

Applicants : GRAF & CIE. A.-G., OF ALTE JONASSTRASSE, CH-8640 RAPPERSWIL, SWITZERLAND.

Inventors : WERNER SIEGRIST.

Application No. 758/Cal/80 filed July 1, 1980.

Appropriate Office for Opposition Proceedings (Rule 4, Patent Rules, 1972) Patent Office, Calcutta.

7 Claims.

A card clothing for carding machines including a plurality of flexible card wires consisting of staple shaped wire sections of a predetermined wire gauge and each including a pair of legs integrally connected to each other by the staple crown, said legs defining teeth and said staple crown defining the base web of each card wire section, said teeth defining lanes extending in the direction of the flow of the fibers to be carded relative to the card clothing, said card wires being disposed in a pattern-like arrangement into a card fillet, said teeth being arranged in a plurality of groups arranged consecutively relative to said direction of fiber flow, each group comprising a plurality of rows of teeth in a diagonal stitch pattern with each row of teeth defining a line extending perpendicularly to said direction of fiber flow, a given row of teeth in one group being displaced relative to a given row of teeth in another group in said direction of fiber flow, a distance measured perpendicularly to said direction of fiber flow which do not exceed said wire gauge, such that said card clothing comprises no free lanes.

(Compl. specn. 19 pages. Drgs. 3 sheets).

CLASS : 32 E. 152167.
Int. Cl. : C 08 f 1/09, 3/28, 3/30.

SUSPENSION POLYMERIZATION PROCESS FOR MAKING VINYL RESINS FOR USE IN PLASTISOL.

Applicants : THE B.F. GOODRICH COMPANY OF 277 PARK AVENUE, NEW YORK, NEW YORK 10017, UNITED STATES OF AMERICA.

Inventors : MARION GEORGE MORNINGSTAR.

Application No. 1225/Cal/80 filed October 28, 1980.

Appropriate Office for Opposition Proceedings (Rule 4, Patent Rules, 1972) Patent Office, Calcutta.

13 Claims.

A suspension polymerization process for producing polymers of vinyl and vinylidene halides and copolymers thereof with each other or either with one or more vinylidene monomers having at least one terminal $\text{CH}_2=\text{C} <$ grouping for use in plastisole comprising, forming a monomer premix containing

the monomer or monomers to be polymerized, the aqueous reaction medium, a polyvinyl alcohol suspending agent, in the range of 0.5% to 1.5% by weight based on the weight of the monomer(s) being polymerized and a nonionic surfactant as hereinbefore described, having a hydrophile-lipophile balance of less than 3.5, in the range of 0.1% to 1.5% by weight, agitating said premix to form suspended droplets of monomer in the premix, adding an oil-soluble free radical yielding polymerization catalyst as hereinbefore described in an amount in the range of 0.01% to 0.5% by weight to said agitated premix, polymerizing said premix with continued agitation at a temperature in the range of 30°C to 70°C to form an aqueous slurry of dense, spherical and glassy polymer particles having a diameter in the range of 10 to 100 microns, and thereafter recovering said particles from said slurry in the usual manner.

(Compl. Specn. 31 pages. Drg. 1 sheet).

CLASS : 61 H & K. 152168.
Int. Cl. : B 01 d 1/00
F 26 b 21/00.

PROCESS FOR DRYING PARTICULATE ORGANIC SOLID MATERIALS PARTICULARLY BROWN COAL.

Applicants : VOEST-ALPINE AKTIENGESSELLSCHAFT OF A-1011 VIENNA FRIEDRICHSTRASSE 4, AUSTRIA.

Inventors : 1. ALOIS JANUSCH AND 2. FRANZ WOLFGANG MAYER.

Application No. 1160/Cal/80 filed October 14, 1980.

Appropriate Office for Opposition Proceedings (Rule 4, Patents Rules, 1972) Patent Office, Calcutta.

13 Claims.

A process for drying a particulate organic solid material particularly brown coal by using steam, wherein the organic solid material having a maximum grain size of 50 mm is continuously suspended with water and heated in a first drying stage to a temperature of at least 100°C under super-atmospheric pressure, and the resulting suspension or sludge is subsequently passed through a second drying stage under the same or increased pressure and thereafter passed through a third drying stage at super-atmospheric pressure wherein it is centrifuged, CO₂ generated in the individual drying stages being discharged or vented heating being effected in the said second and third drying stages by supplying steam thereof, and continuously discharging the separated solid materials from the last drying stage and pressure is released, and final drying is effected by the action of air in an aeration stage.

(Compl. specn. 25 pages. Drgs. 4 sheets).

CLASS : 40 F, 61 B. 152169.
Int. Cl. : B 01 j 1/00
F 26 b 17/00, 21/00.

APPARATUS FOR DRYING PARTICULATE ORGANIC MATERIAL PARTICULARLY BROWN COAL.

Applicants : VOEST-ALPINE AKTIENGESSELLSCHAFT OF A-1011 VIENNA, FRIEDRICHSTRASSE 4, AUSTRIA.

Inventors : ALOIS JANUSCH.

Application No. 1161/Cal/80 filed October 14, 1980.

Appropriate Office for Opposition Proceedings (Rule 4, Patents Rules, 1972) Patent Office, Calcutta.

15 Claims.

Apparatus for drying particulate organic materials, particularly brown coal, by means of steam and of hot water, comprising a space maintained under a pressure exceeding atmospheric pressure, through which space the organic materials are, preferably continuously, fed in form of a sludge or suspension and in which space the organic materials are at least partially separated from the water, characterized in that at the upper end of the space maintained under a pressure exceeding atmospheric pressure at least one supply opening is provided and that at the lower end of said space at least one discharge opening for solid materials is

provided and in that between said supply opening and said discharge opening sieves are obliquely arranged which are roofing chambers limited by water-impermeable and preferably heat-insulating walls and having drain channels connected thereto and in that further a plurality of sieves is arranged in the manner of cascades one above the other, the bottom edges of the sieves being located above the most elevated area of the sieve arranged immediately below each sieve considered.

(Compl. specn. 12 pages. Drg. 1 sheet).

CLASS : 47 C. 152170.
Int. Cl. : C 10 b 25/16.

CLOSING AND OPENING DEVICE FOR USE IN COKE OVENS.

Applicants : DR. C. OTTO & COMP. GMBH OF CHRISTSTRASSE 9, 4630 BOCHUM, WEST GERMANY.

Inventors : THEO RODDENBERG AND DIETER JANSSEN.

Application No. 580/Cal/81 filed May 30, 1981.

Appropriate Office for Opposition Proceedings (Rule 4, Patents Rules, 1972) Patent Office, Calcutta.

1 Claim.

A device in coke ovens for consecutively closing the seal of the main and opening the cover of the gas off take pipe and activating such cover and seal in the opposite sense and converse sequence, characterised by :

(a) Two draw rods (18, 30) form by way of forked ends (31, 32) an articulation (29) and pivoted therein in a plane perpendicular to the axis of the main (13).

(b) The bottom draw rod (18) being raised and lowered, downwards movement of the draw rods (18, 30) leading first to closure of the main seal (15), then to opening of the offtake pipe cover (14), whereas upwards movement of the draw rods (18, 30) leads first to closure of such cover (14) then to the opening of the main seal (15).

(c) The pivot pin (26) has mounted on it, proceeding from the outside to the inside, the fork ends (31) of the bottom draw rod (18), the fork ends (32) of the top draw rod (30) and in the centre a bell crank lever, the same being mounted through the agency of a slot (23) extending along the length of one arm (35) of the bell crank lever, the arm being of flat bar stock, a pair of rails (19) or the like being provided symmetrically of the draw rods (18, 30) on a wall disposed laterally of the offtake pipe (11) in order to guide the pivot pin (26) vertically,

(d) The seal (15) of the main being attached to the other arm (20) of the bell crank lever, the same being pivotable around the attachment position (25),

(e) The top draw rod (30) having at its end an elongated eye (22) serving to guide the end (27) of an arm disposed on a shaft (28) serving to guide the weight-loaded gas offtake pipe cover (14).

(Compl. specn. 8 pages. Drgs. 4 sheets).

CLASS : 9 D. 152171.
Int. Cl. : C 21 b 1/00, 21/00.

A PROCESS FOR PREPARATION OF IMPROVED ALUMINIUM SILICON BASE ALLOYS.

Applicants & Inventors : DUAL MUKHERJEE, C/O SI. L. B. MUKHERJEE, C.I.T. BUILDINGS (OLD) BLOCK NO. 7/B, FLAT NO. 32, BELIAGHATA, PIN 700010, CALCUTTA-10.

Application No. 839/Cal/81 filed July 25, 1981.

Appropriate Office for Opposition Proceedings (Rule 4, Patents Rules, 1972) Patent Office, Calcutta.

6 Claims.

A process for the preparation of aluminium silicon base alloys having silicon in the range of 8 to 25% by weight of

the total alloy, which comprises treating the alloy before casting with an inoculating agent characterized in that an inoculating agent as herein described is used in an amount not exceeding 1% by weight of the total alloy.

(Compl. specn. 11 pages. Drgs. 1 sheet).

CLASS : 85 J & R.

152172.

Int. Cl. : C 21 b 7/00, F 27 b 1/10.

AERATION FEEDER FOR SUPPLYING PULVERIZED COAL TO BLAST FURNACE HEARTH.

Applicants : DONETSKY NAUCHNO-ISSLEDOVATELSKY INSTITUT CHERNOI METALLURGII OF DONETSK, BULVER SHEVCHENKO, 26, USSR AND DONETSKY POLIT-EKHNICHESKY INSTITUT OF DONETSK, LUTISA ARTEMA, 58, USSR.

Inventors : 1. STANISLAV LVOVICH YAROSHEVSKY 2. ALEXEI MIRTEFVICH KAMARDIN 3. LEO

said lower wall portion, said annular array of gripper means being operable to engage and grip a tread and a radial tread ply band disposed centrally of said annular array of gripper means upon expansion of said tube element, said tube element when expanded effecting a decrease in diameter of said annular array of gripper means and when contracted effecting an increase in the diameter of said annular array of gripper means to thereby effect the release of a gripped tread and radial tread ply band, a plurality of ply bands disposed only in said lower wall portion adjacent said plurality of gripper means to increase the rigidity of said lower wall portion to provide for uniform radial movement of said lower wall portion and said gripper means disposed thereon upon expansion of said tube element to effect gripping of a tread and a radial tread ply band thereby and to prevent collapse of said tube element upon contraction.

(Compl. specn. 19 pages. Drgs. 1 sheet).

CLASS : 123.

152174

Int. Cl. : C 05 b 1/06

R is selected from the group consisting of hydrogen, halogen, C₁-C₄ alkyl, acetyl, trifluoromethyl, nitro, C₁-C₄ alkoxy, C₁-C₄ alkylthio, C₁-C₄ sulfonyl

said support means including fixed support bars beneath the grate means which extend across the width of the furnace and are attached to and supported by the side walls of the

Ind. CLASS : 80 I.

152180.

3 Claims

Int. CLASS : B01D 35/00.

AN IMPROVED FLUID FILTERING DEVICE.

Applicant & Inventor : ISHWERIAL NICHHABHAI PATEL, INDIAN NATIONAL, BLOCK NO 2 "MAHESHWAR DEEP", PLOT 75, R. B MEHTA ROAD, GHATKOPAR (EAST) BOMBAY-77, MAHARASHTRA, INDIA.

Application No. 301/BOM/80 filed on Sept 26, 1980.

Complete after Provisional left on Dec 24, 1981.

Appropriate office for opposition proceedings (Rule 4, Patents Rule 1972) Patent Office, Bombay Branch.

11 Claims.

An improved fluid filtering device for specified filtration of various fluids comprises an housing having an upper portion or head and a lower portion detachably attached to the said head, an inlet nozzle provided in the top centre of head, an outlet nozzle provided in the side of head, a filtering cartridge detachably attached in the bottom centre of the head; the said filtering cartridge consists of a hollow body having a plurality of open faces or sides, each of them provided with, a filter supporting plate preferably made of moulded plastics with fine mesh to pass through the filtered fluid, a filter plate of desired pore sizes and a cover plate preferably made of moulded plastics with fine mesh to allow the fluid to be filtered to enter filtering cartridge, the filtering cartridge is connected to the said head through a nipple connecting the central space of the filtering cartridge with the outlet nozzle to pass out the filtered fluid.

(Provisional Specification 2 Pages, Drawings 2 Sheets.

Complete Specification 9 Pages, Drawings 5 Sheets).

CLASS 24 F.

152181.

Int. CLASS B 60 t 11/00.

A SERVO BOOSTER FOR VEHICLE BRAKING SYSTEM.

Applicant : LUCAS INDUSTRIES LIMITED, GREAT KING STREET, BIRMINGHAM 19, ENGLAND.

Inventors : (1) DAVID JOHN PARKER, (2) ERIC MARTIN LILLEY.

Application No. 35/Mas/81 filed February 23, 1981.

Convention date : (23.2.1980) (No. 8006183 United Kingdom).

15 Claims.

A servo booster for a vehicle braking system, comprising housing containing a movable wall having sealing means

A method to make a self-standing collapsible pouch from three rolls of heat-sealable sheets, the method comprising assembly of the sheets (designated A, B, and C for reference) from the corresponding rolls, sheets A and B being of equal width and sheet C being of smaller predetermined width and folded midway, the folded sheet C being disposed between the sheets A and B so that edges of the sheets A, C and B are disposed in one vertical plane, sheets A, C and B being made to run intermittently with folded sheet C and corresponding portions of sheets A and B being made to pass between two sealing plates of a heat-sealing mechanism, the plates being rectangular and of width equal to that of the folded sheet C, characterised in that each plate has an identical concave cut-out at its inner edge, the depth of the cut-out being determined by the folded width of sheet C, a heat-proof flat partition (designated D for reference) of the size of the plates being located between them and adapted to keep apart the folds of sheet C, the two plates being made to press between them the portion of sheet A, the sheet C with partition D between its folds and portion of sheet B, sealing the portions of said sheets above and below the partition D adapted so as to become the base of the pouch, the plates being then taken apart after sealing the sealed portions of the sheets A, C and B being drawn out by known means bringing portions of sheets A, C and B between the plates for next operation, the drawn-out sheets A, C and B being transversely sealed and midway between two consecutive sealed base portions adapted to separate the pouch.

(Complete specification 9 pages; Drawing 1 sheet).

Ind. Class : 62 B

152183

Int. Class : B05 c 11/00.

AN IMPROVED HIGH TEMPERATURE HIGH-PRESSURE BFAM DYEING PLANT.

Applicant & Inventor : DEVENDRA SOMABHAI NAIK, 77, JAI AMBE SOCIETY, ADAJAN ROAD, SURAT-395009, GUJARAT, INDIA.

Application No. : 59/BOM/80 Filed on March 15, 1982.

(Post dated to April 22, 1982).

Complete after provisional left on 19th Jan, 1983.

Appropriate office for opposition proceedings (Rule 4, Patents Rule 1972) Patent office, Bombay branch.

9 Claims**Claim 1**

An improved high temperature high pressure beam dyeing plant comprising an autoclave for dyeing fabric containing perforated beam; a heat exchanger; a liquor circulating pump. A closed main pipe line connecting the said autoclave, the said heat exchanger and the said pump for circulating

Application No. 247/Cal/79 filed March 14, 1979.

Appropriate Office for Opposition Proceedings (Rule 4, Patents Rules, 1972) Patent Office, Calcutta.

4 claims

A bobbin hanger, which comprises, a bobbin-holding barrel being inserted into a hole of a bobbin and hanging said bobbin by fingers projecting out of the lower part of the outer circumferential surface of said holding barrel and a securing member through which said holding barrel is attached to a shank rotatably and swingably; characterised in that said securing member is provided at its lower end with a bearing race-receiving spherical surface and is suspended through the medium of both said shank provided with a neck and a round trunk part from said bearing race-receiving spherical surface upward and a ball bearing having a retainer provided on said bearing race-receiving spherical surface; the top part of said securing member is provided with a through hole at an interval of a broad clearance between itself and said shank and the peripheral region of said through hole is formed with a spherical surface concentric with said bearing race-receiving spherical surface formed at the lower end of said shank; and a cap plate, which has through-hole formed leaving a narrow gap between itself and said round trunk part of said shank and is formed with a concaved spherical surface substantially parallel with the spherical top surface of said securing member, which cap plate mounted on the top face of said securing member and is arranged a coiled spring on its top face, thereby said cap plate being able to be pressed to the side of said securing member by said coiled spring.

(Compl. specn 20 pages. Digs. 2 sheets).

PATENTS SEALED

143021 148726 150132 150647 150650 150699 150729 150760
150784 150785 150810 150811 150855 150908 150961 150977
151019 151044 151049 151065 151079

RENEWAL FEES PAID

116816	116944	117879	117889	117904	117913	117957
117961	118004	118005	118144	118196	118205	118253
118266	118335	118363	118379	118604	118720	118737
118742	118844	118999	119031	119110	119194	119387
119456	119663	120469	120556	120975	122046	122248
122253	122314	122720	122766	123205	123399	123453
123453	123744	123855	123907	124015	124204	124589
128057	128073	128308	128426	128699	128790	128864
128873	128907	128932	129066	129264	129331	129389
129600	129712	129842	129843	130926	132414	132617
133114	133168	133173	133182	133347	133566	133714
133740	135227	135355	135388	135411	135472	135805
135880	136198	136205	136301	136428	136436	136662
136705	136706	136963	137058	137088	137099	137254
137416	137469	137492	137500	137527	137588	137679
137738	137954	138095	138108	138152	138333	138544
138849	138997	139417	139618	139894	139965	140096
140133	140180	140589	140646	140656	140689	140780
141056	141139	141540	141594	141649	141699	142035
142172	142308	142331	142403	142405	142434	142607
142657	142803	142840	142970	142976	142995	143239
143268	143367	143378	143565	143650	143687	143695
143737	143740	143745	143947	143806	143818	143826
143931	144036	144075	144097	144117	144171	144230
144231	144326	144396	144400	144422	144479	144527
144551	144634	144939	144967	144969	144985	145006
145051	145113	145230	145256	145376	145640	145726
145738	145753	145759	145790	145795	145796	145832
145931	145979	146099	146141	146221	146225	146255
146259						

149694 149716 149735 149762 149790 149849 149858 149869
149870 149871 149873 149881 149883 149900 150036 150065
150086 150093 150177 150182 150190 150242 150249 150253
150258 150262 150281 150263 150282 150284 150285 150286
150326 150336 150338 150341 150342 150343 150344 150345
150347 150351 150352 150355 150395 150404 150405 150408
150410 150422 150451 150530 150556 150585 150586 150603
150631 150635 150636 150713 150717 150779 150798 150790
150848

CESSATION OF PATENTS

113500 113506 113512 113513 113526 113527 113530 113532
113560 113565 113578 113581 113584 113605 113616 113619
113620 113626 113630 113637 113638 113639 113643 113652
113655 113661 113665 123458 139588 142074

RESTORATION PROCEEDINGS

(1)

Notice is hereby given that an application for restoration of Patent No. 148029 dated the 31st January, 1978 made by Girling Limited on the 12th January, 1983 and notified in the Gazette of India, Part-III, Section 2, dated the 23rd April, 1983 has been allowed and the said patent restored.

(2)

Notice is hereby given that an application for restoration of Patent No. 148984 dated the 14th May, 1979 made by Guest Keen Williams Limited on the 22nd February, 1983 and notified in the Gazette of India, Part-III, Section 2 dated the 28th May, 1983 has been allowed and the said patent restored.

REGISTRATION OF DESIGNS

The following designs have been registered. They are not open to inspection for a period of two years from the date of registration except as provided for in Section 50 of the Design Act, 1911.

The date shown in the each entry is the date of registration of the design included in the entry.

Class 1. No. 152963. K. W. Engineering Works (Regd.), an Indian Partnership firm, Opposite Industrial Estate, Link Road, Ludhiana (Punjab) India. "Chain Wheel Set". 4th April, 1983.

Class 1. No. 153310. TT (Private) Limited, Dooravaninagar, Bangalore 560 016, Karnataka, India, a Company duly organised and existing under the laws of the Union of India. "Pressure Cookers". 28th July, 1983.

Class 1. No. 152994. Deshraj Gupta & Co. Pvt. Ltd., of 4634 Ajmeri Gate, Delhi-110006, India, an Indian Company. "Pressure Regulator Valve for use with LPG Cylinder". 13th April, 1983.

Class 1. No. 152939. Glass Equipment (India) Ltd., having a registered office at 603, Deep Sikha, 8-Rajendra Place, New Delhi-110008, India. "Take Out Tong Holder". 26th March, 1983.

Class 1. No. 153125. Maya Panchal Industries, 216A Falkland Road, Sanghvi Godown Khethwadi, 10th Lane Bombay 400 004, Maharashtra, India, a registered Partnership firm. "Tea Ball". 24th May, 1983.

Class 3. No. 152769. General Plastics (P) Ltd., Old Post Office Road, Udupi 576 101, Karnataka, India, an Indian Company. "Fishing Flots". 16th February,

Class 3. No. 153394. Eagle Flask Private Limited, (an existing Company under the Companies Act) at Eagle Estate, Talegaon-410 507, District Pune, Maharashtra State, India. "Vacuum Flask". 26th August, 1983.

Class 3. No. 153395. Eagle Flask Private Limited, (an existing Company under the Companies Act) at Eagle Estate, Talegaon-410 507, District Pune, Maharashtra State, India. "Vacuum Flask". 26th August, 1983.

Class 3. No. 153396. Eagle Flask Private Limited, (an existing Company under the Companies Act) at Eagle Estate, Talegaon-410 507, District Pune, Maharashtra State, India. "Vacuum Flask". 26th August, 1983.

Class 3. No. 153397. Eagle Flask Private Limited, (an existing Company under the Companies Act) at Eagle Estate, Talegaon-410 507, District Pune, Maharashtra State, India. "Vacuum Flask". 26th August, 1983.

Class 3. No. 153386. Eagle Flask Private Limited, (an existing Company under the Companies Act) at Eagle Estate, Talegaon-410 507, District Pune, Maharashtra State, India. "Vacuum Flask". 26th August, 1983.

Class 3. No. 153387. Eagle Flask Private Limited, (an existing Company under the Companies Act) at Eagle Estate, Talegaon-410 507, District Pune, Maharashtra State, India. "Vacuum Flask". 26th August, 1983.

Class 3. No. 153388. Eagle Flask Private Limited, (an existing Company under the Companies Act) at Eagle Estate, Talegaon-410 507, District Pune, Maharashtra State, India. "Vacuum Flask". 26th August, 1983.

Class 3. No. 153389. Eagle Flask Private Limited, (an existing Company under the Companies Act) at Eagle Estate, Talegaon-410 507, District Pune, Maharashtra State, India. "Vacuum Flask". 26th August, 1983.

Class 3. No. 153390. Eagle Flask Private Limited, (an existing Company under the Companies Act) at Eagle Estate, Talegaon-410 507, District Pune, Maharashtra State, India. "Vacuum Flask". 26th August, 1983.

Class 3. No. 153391. Eagle Flask Private Limited, (an existing Company under the Companies Act) at Eagle Estate, Talegaon-410 507, District Pune, Maharashtra State, India. "Vacuum Flask". 26th August, 1983.

Class 8. No. 153043. Aspinwall & Company (Travancore) Limited, P.O. Box No. 5, Chavadi Parambu, C.C.N.B. Road, Alleppey-688 001, Kerala State, An Indian Company. "Carpet". 21st April, 1983.

Class 8. No. 153044. Aspinwall & Company (Travancore) Limited, P.O. Box No. 5, Chavadi Parambu, C.C.N.B. Road, Alleppey-688 001, Kerala State, An Indian Company. "Carpet". 21st April, 1983.

EXTENSION OF COPYRIGHT FOR THE THIRD PERIOD OF FIVE YEARS

Nos. 145021, 145022, 145023, 145024.—Class-4.

DR. K. V. SWAMINATHAN
Controller General of Patents,
Designs and Trade Marks